



# LEICA GEOVID 42 R

## Technical data



Rangefinder	Leica Geovid 8x42 R	Leica Geovid 10x42 R
Order no.	40 425 (meter version) 40 426 (yard version)	40 427 (meter version) 40 428 (yard version)
Package includes	contoured neoprene carrying strap front lens caps, eyepiece caps, battery, Cordura case	contoured neoprene carrying strap front lens caps, eyepiece caps, battery, Cordura case
Magnification	8 x	10 x
Front lens diameter	42 mm	42 mm
Exit pupil	5.25 mm	4.2 mm
Twilight factor	18.3	20.5
Field of view at 1,000 yds/m	368 ft / 125 m	331 ft / 110 m
Close focus range	approx. 18.4 ft / 5.6 m	approx. 18.4 ft / 5.6 m
Diopter compensation	± 4 dpt	± 4 dpt
Distance measurement:		
Range	10 yds to approx. 1,200 yds / 10 m to approx. 1,100 m	10 yds to approx. 1,200 yds / 10 m to approx. 1,100 m
Equivalent horizontal range (EHR)	10 yds to 1,200 yds / 10 m bis 1,100 m	10 yds to 1,200 yds / 10 m bis 1,100 m
Measuring accuracy	± 1 yd / m to 382 yds / 350 m ± 2 yds / m to 766 yds / 700 m ± 0,5 % beyond 766 yds / 700 m	± 1 yd / m to 382 yds / 350 m ± 2 yds / m to 766 yds / 700 m ± 0,5 % beyond 766 yds / 700 m
Display	LED display with 4 characters and ambient-light-controlled brightness	LED display with 4 characters and ambient-light-controlled brightness
Eyecup with twist-and-pull action	yes, detachable, with 2 click-stops	yes, detachable, with 2 click-stops
Eyepieces for eyeglass wearers	yes	yes
Focusing	internal focusing with center focusing barrel	internal focusing with center focusing barrel
Coating	HDC® multicoating	HDC® multicoating
Waterproof	waterproof to 16.5 ft / 5 m	waterproof to 16.5 ft / 5 m
Body	aluminium, nitrogen-filled	aluminium, nitrogen-filled
Dimensions (W x H x D)	4.9 x 6.8 x 2.8 in / 125 x 173 x 70 mm	4.9 x 6.6 x 2.8 in / 125 x 168 x 70 mm
Weight	approx. 33.5 oz / 950 g incl. battery	approx. 33.3 oz / 945 g incl. battery
Laser	eye-safe, invisible light laser compliant with EN and FDA Class 1	eye-safe, invisible light laser compliant with EN and FDA Class 1
Measuring mode	scan mode, single measurement	scan mode, single measurement
Power supply	1 x 3 V / CR2 lithium button cell	1 x 3 V / CR2 lithium button cell
Battery life	approx. 2,000 measurements at 68° F / 20°C	approx. 2,000 measurements at 68° F / 20°C
Accessories	tripod adapter (42 220) floating carrying strap (42 163)	tripod adapter (42 220) floating carrying strap (42 163)